



USB 2.0 C-mount and Eyepiece Microscope Camera

General specifications	USB output	Yes
	C-Mount	Yes
	Housing	Aluminium
	Dimensions (mm)	58 x 58 x 36.4
	Weight (kg)	0.18

Sensor	Camera resolution (n° of pixels: W x H)	2592x1944
	Color / Monochrome	Color
	Sensor Size	1/2.5"
	Sensor Technology	CMOS
	Sensor Type	APTINA CMOS
	Image Format	4/3
	Pixel Size (µm)	2.2x2.2
	Acquisition technology	Rolling shutter
	Sensitivity	0.53 V/lux-second
	Signal/Noise Ratio (DB)	40.5
	Dynamic range (DB)	66.5
	ADC conversion	8 Bit
	Color Depth	1, 4, 8, 24 Bit
	Exposure time	0.294 msec - 2 sec
	Binning	1x1; 2x2; 4x4
IR filter	Yes	
IR filter range (nm)**	380-650 (IR CUT)	

**** If used for red emission fluorescence wavelengths above 650nm please order it by specifying with "AR GLASS"**

USB	PC Camera resolution (MP)	5.1
	USB standard	USB2.0
	Frame rate full resolution (fps)	7@2592x1944
	Frame rate other resolution (fps)	27@1280x960; 90@640x480

Camera Power Supply	Connector	USB
	Output voltage	PC USB

Camera accessories	Optical adapter (for 23mm eyepiece tube)	0.5x
	Adapter ring	Yes
	Diameter of adapter ring (mm)	30
	Diameter of adapter ring (mm)	30.5
	Calibration slide	Yes
	USB cable (1.8m)	Yes

Environment	Working Temperature	-10°C up to +50°C
	Storage Temperature	-20°C up to +60°C
	Relative Humidity	30% to 80%
	Storage Humidity	10% to 60%

Operating System	OS	Windows 7
	OS	Windows 8
	OS	Windows 10 (32Bit)
	OS	Windows 10 (64Bit)
	OS	Windows 11
	OS	Osx (MAC Osx) starting from 10.7.5 (only LITEVIEW)
	OS	Linux (only LITEVIEW)

Available Software	PC SW	PROVIEW
	PC SW	LITEVIEW

PC requirements	PC	CPU: Intel Core2 - 2.8GHz or higher
	PC	RAM: 2GB or more
	PC	USB 2.0